

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : SpraySeal
Product code : F-300 Series

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Protective coating

1.3. Supplier

Manufacturer:

NaturaSeal Distribution Inc.
960 Edgeley Blvd. Unit #4
Vaughan, ON L4K 4V4 - Canada
1 905 827 7221

Naturaseal Building & Construction Materials LLC
The Offices at IBN Battuta Gate, 804B
P.O. Box: 214771, Jebel Ali First
Dubai, United Arab Emirates

1.4. Emergency telephone number

Emergency number : CANADA - 1-855-797-SEAL (24hrs) (1-855-797-7325)
U.A.E - +971 4 568 1384

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin sensitization, Category 1 May cause an allergic skin reaction

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning
Hazard statements (GHS US) : May cause an allergic skin reaction
Precautionary statements (GHS US) : Avoid breathing mist, spray, vapours.
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Carcinogenicity only applies to roofing and paving operations where the asphalt is heated.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Asphalt	(CAS-No.) 8052-42-4	40 - 70	Carc. 2, H351
Rosin	(CAS-No.) 8050-09-7	0.5 - 2	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Sens. 1, H317

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration as needed. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. May cause slight temporary irritation.
Symptoms/effects after eye contact	: May cause slight temporary irritation.
Symptoms/effects after ingestion	: May cause gastric irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: None known.

5.2. Specific hazards arising from the chemical

Fire hazard	: On combustion, forms: carbon oxides (CO and CO ₂).
Explosion hazard	: No direct explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so.
------------------	-------------------------------

6.1.1. For non-emergency personnel

Protective equipment	: For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ensure adequate air ventilation.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Dispose of this material and its container at hazardous or special waste collection point.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations".

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep container closed when not in use. Avoid breathing mist, spray, vapors.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Storage conditions : Store tightly closed in a dry, cool and well-ventilated place.

Incompatible materials : None known.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Asphalt (8052-42-4)		
ACGIH	Local name	Asphalt (Bitumen) fumes, as benzene-soluble aerosol
ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m³ (fume, inhalable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr. Notations: A4 (Not classifiable as a Human Carcinogen); BEIP
ACGIH	Biological Exposure Indices (BEI)	Parameter: 1-Hydroxypyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (nonquantitative)
ACGIH	Regulatory reference	ACGIH 2019
NIOSH	NIOSH REL (ceiling) (mg/m³)	5 mg/m³ (fume)
Rosin (8050-09-7)		
ACGIH	Local name	Rosin core solder thermal decomposition products (colophony)
ACGIH	Remark (ACGIH)	Exposure by all routes should be carefully controlled to levels as low as possible. TLV® Basis: Skin sens; dermatitis; asthma. Notations: DSEN; RSEN
ACGIH	Regulatory reference	ACGIH 2019

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Impermeable protective gloves.

Eye protection:

Chemical goggles or safety glasses.

Skin and body protection:

Long sleeved protective clothing

Respiratory protection:

An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: Viscous.
Color	: brown
Odor	: Slight resinous
Odor threshold	: No data available
pH	: 10 - 12 in water (approximately)
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C Water
Flash point	: > 260 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 1 mm Hg @ 20 °C
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1 Approximately
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

On combustion, forms: carbon oxides (CO and CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Asphalt (8052-42-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 94.4 mg/m ³ (Exposure time: 4.5 h)

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rosin (8050-09-7)	
LD50 oral rat	7600 mg/kg
LD50 dermal rabbit	> 2500 mg/kg
LC50 inhalation rat (mg/l)	1.5 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 10 - 12 in water (approximately)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 10 - 12 in water (approximately)
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified. (Based on available data, the classification criteria are not met) Carcinogenicity only applies to roofing and paving operations where the asphalt is heated.

Asphalt (8052-42-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity – single exposure	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity – repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Viscosity, kinematic	: No data available
Likely routes of exposure	: Ingestion. Inhalation. Skin and eye contact.
Symptoms/effects after inhalation	: Inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. May cause slight temporary irritation.
Symptoms/effects after eye contact	: May cause slight temporary irritation.
Symptoms/effects after ingestion	: May cause gastric irritation.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: This material has not been tested for environmental effects.
-------------------	--

Rosin (8050-09-7)	
EC50 Daphnia 1	3.8 - 5.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Asphalt (8052-42-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	> 6

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Asphalt (8052-42-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Rosin (8050-09-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List)

Rosin (8050-09-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Asphalt (8052-42-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Rosin (8050-09-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Asphalt (8052-42-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

Rosin (8050-09-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

SpraySeal

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05 July 2019

Full text of H-phrases:

H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.